

Contents

Acknowledgments	V
Preface	VII
1 Materials for Blown Film	1
1.1 Polymers	1
1.1.1 Polyethylene (PE)	2
1.1.1.1 Low Density Polyethylene (LDPE)	2
1.1.1.2 High Density Polyethylene (HDPE)	4
1.1.1.3 Linear Low Density Polyethylene (LLDPE)	5
1.1.1.4 Medium Density Polyethylene (MDPE)	6
1.1.1.5 Metallocene Polyethylene (mPE)	6
1.1.2 Polypropylene (PP)	6
1.1.3 Polystyrene (PS)	7
1.1.4 Ethylene Vinyl Acetate (EVA)	8
1.1.5 Ethylene Vinyl Alcohol (EVOH)	9
1.1.6 Polyvinyl Chloride (PVC)	9
1.1.7 Polyvinylidene Chloride (PVDC)	10
1.1.8 Polyamide (PA)	10
1.1.9 Polyurethane (PU)	11
1.2 Additives	11
1.2.1 Antiblocking Agents	12
1.2.2 Antioxidants	12
1.2.3 Antistatic Agents	12
1.2.4 Colorants	13
1.2.5 Lubricants	14
1.2.6 Reinforcements and Fillers	14
1.2.7 Stabilizers	16
1.2.8 Tackifiers	16

2	Polymer Rheology	19
2.1	Basic Concepts	19
2.2	Variables Influencing Viscosity	22
2.2.1	Process Conditions	23
2.2.2	Molecular Structure	24
2.2.2.1	Molecular Weight	25
2.2.2.2	Molecular Weight Distribution	26
2.2.2.3	Chain Branching	28
2.3	Rheology in Blown Film Extrusion	29
2.3.1	Inside the Extruder and Die	30
2.3.2	In the Bubble	30
3	Extrusion Overview	33
3.1	Extruder Hardware Systems	33
3.1.1	Drive System	35
3.1.1.1	Motor	35
3.1.1.2	Speed Reducer	35
3.1.1.3	Thrust Bearing	36
3.1.2	Feed System	38
3.1.3	Screw/Barrel System	39
3.1.3.1	Screw	40
3.1.3.2	Barrel	41
3.1.4	Head/Die System	43
3.1.4.1	Head Assembly	44
3.1.4.2	Adapter	44
3.1.4.3	Breaker Plate	44
3.1.4.4	Melt Filter	45
3.1.4.5	Die	47
3.1.5	Instrumentation and Control System	47
3.1.5.1	Temperature Control	48
3.1.5.2	Head Pressure	51
3.1.5.3	Motor Current	53
3.2	Inside the Extruder	53
3.2.1	Solids Conveying	54
3.2.1.1	Gravity-Induced Region	55
3.2.1.2	Drag-Induced Region	56
3.2.2	Melting	57
3.2.3	Melt Pumping	59
3.2.4	Mixing	60
3.2.4.1	Distributive Mixing	61

3.2.4.2	Dispersive Mixing	62
3.2.4.3	Mixing Devices	63
3.2.5	Degassing	64
3.2.6	Die Forming	65
4	Hardware for Blown Film	69
4.1	Upstream Components	70
4.2	Grooved Feed Throat	72
4.3	Screws for Blown Film Extrusion	74
4.4	Blown Film Dies	75
4.5	Bubble Geometry	80
4.6	Bubble Cooling	83
4.7	Bubble Stabilization	89
4.8	Collapsing Frames	90
4.9	Haul-off	91
4.10	Winders	92
4.11	Film Treatment	93
4.12	Line Control	94
5	Processing	101
5.1	Process Variables vs. Bubble Geometry	102
5.2	Characteristic Bubble Ratios	103
5.3	Process/Structure/Property Relationships	107
5.4	Double Bubble Processing	109
6	Coextrusion	111
6.1	Dies	112
6.2	Interfacial Instabilities	114
6.3	Product Applications	115
6.3.1	Breathable Packaging	115
6.3.2	Shrink Film	116
6.3.3	High Barrier Film	116
7	Film Properties	119
7.1	Tensile Strength (ASTM D882)	120
7.2	Elongation (ASTM D882)	123

7.3	Tear Strength (ASTM D1004, D1922, and D1938)	123
7.4	Impact Resistance (ASTM D1709, D3420, and D4272)	125
7.5	Blocking Load (ASTM D3354) and Coefficient of Friction (ASTM D1894) ..	126
7.6	Gel (Fisheye) Count (ASTM D3351 and D3596)	127
7.7	Low Temperature Brittleness (ASTM D1790)	127
7.8	Gloss (ASTM D2457)	128
7.9	Transparency (ASTM D1746)	128
7.10	Haze (ASTM D1003)	128
7.11	Density (ASTM D1505)	129
7.12	Melt Flow Rate (ASTM D1238)	130
7.13	Viscosity by Capillary Rheometry (ASTM D3835)	132
8	Troubleshooting	135
8.1	Extruder Problems	136
8.1.1	Surging	136
8.1.2	High Melt Temperature	137
8.1.3	Excessive Cooling	139
8.1.4	Low Output	139
8.2	Film Problems	140
8.2.1	Melt Fracture	141
8.2.2	Thickness Variation	141
8.2.3	Die Lines	146
8.2.4	Gels	146
8.2.5	Low Mechanical Properties	147
8.2.6	Poor Optical Properties	149
8.2.7	Wrinkles	150
9	Appendices	151
9.1	Appendix 1: The Blown Film Extrusion Simulator	151
9.1.1	Introduction	151
9.1.2	Download and Installation	152
9.1.3	Running the Program	153
9.1.4	Worksheet	159
9.2	Appendix 2: Useful Equations	162
	References	171
	Index	175